

CHAPTER 8 FUGITIVE PARTICULATE

Subchapter 3 - Road Maintenance Inside the Area of Regulated Road Sanding Materials

Rule 8.301 - Deicer Required

- (1) When the ambient temperature is above 10°F, a person may not apply street sanding materials other than an approved deicer to those public roadways in the required deicing zone, except under extraordinary circumstances.

Rule 8.302 - Durability Requirements

- (1) A person may not place any sanding or chip sealing materials upon any road or parking lot located inside the area of regulated road sanding materials that has a durability of less than or equal to 80 as defined by AASHTO T-210 procedure B and a silt content passing the #200 sieve of greater than 2.5% as defined by AASHTO T-27 and T-11.

Rule 8.303 - Street Sweeping Requirements

- (1) Between December 1 and March 31, when the paved road surface is above 32°F for longer than four hours, political subdivisions shall clean the center line and areas immediately adjacent to the travel lane of any major arterials they maintain inside the area of regulated road sanding materials.
- (2) The Control Board hereby incorporates Chapter 10.50 of the Missoula Municipal Codes which requires street sweeping.

Rule 8.304 - Contingency Measure

- (1) The area of regulated road sanding materials defined by Rule 8.101(2) is expanded to include Section 1, T12N R20W, Sections 5 and 24, T13N R19W, Sections 19, 24, 25, 30, 31 and 36, T13N R20W.